



Activo installation guide

Included in the set:

- 1 x filter housing
- 2 x fittings (pre-installed)
- 2 x hoses
- 1 x wrench
- 1 x wall bracket
- 1 x filter cartridge

1:

Insert the filter cartridge into the filter housing, then assemble the bottom and top parts. Make sure the cartridge is centered in the housing. If it is tilted, it will be difficult to assemble the top and bottom, and the cartridge will need to be adjusted. Use the included wrench to tighten properly.

2:

The filter housing can be mounted on the wall under the kitchen sink using the included wall bracket. If you choose to mount the filter, make sure there is enough space beneath it to replace the filter cartridge later. The filter housing can also be placed under the sink without being mounted.

3: Installation:

Turn off the water supply to the cold water outlet, either via the main valve or, if available, a small valve under the sink.

Then disconnect the cold water hose.

Attach the included hoses to each side of the filter housing. Pay attention to the arrows on top of the filter housing, which indicate the direction the water should flow.

The two included hoses are not identical – one fits your cold water tap, and the other is used to connect the filter housing to the loose hose from the tap.

Once both hoses are attached and tightened to the filter housing, connect the inlet hose to your cold water outlet. Then connect hose 2 from the filter housing to the loose hose from your tap that you previously removed from the cold water outlet.

Carefully turn the water back on and check for any leaks. If there is a leak, it may be necessary to tighten the connection where it is leaking.

Let the water run for 5 minutes to flush out any excess carbon from the filter.